## **Declaration of performance**

Number: 2013-045 Rijswaard facing brick



 (4) Manufacturer:

 Steenfabriek De Rijswaard B.V.

 De Rijswaard 2
 Fax: +31 (0)418 - 55 22 21

 NL-5308 LV AALST
 Fax: +31 (0)418 - 55 29 00

 www.rijswaard.nl
 www.rijswaard.nl



(1) Unique identification code of the product- type	Brons/Grijs	
(2) Typenumber	104211013 Gamers Bont HV WF	
(3) Intended use or uses of the construction productbouwproduct	U units for use in unprotected masonry walls, colums and partitions.	
(6) System or systems of assessment and verification of constancy of performance of the construction product	2+	
(7) Notified body	Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.	

(9) Declared performance:				
Dimensions	Waalformat		U Metselbaksteen, Categorie I volgens EN77- 1:2011 + A1:2015	
Length	210	mm		
Width	98	mm		
Height	49	mm		
Dimensional tolerance	Т2			
Range category	R1			
Flatness of bed faces	NPD			
Parallellisme legvlakken	NPD			
Gross dry density	1500	kg/m3		
Net dry density	NPD	kg/m3		
Tolerance Volumetric Mass: Class / %	D1   ±10	%		
Total volume frog	<20%			
Group Eurocode	1			
Mean compressive strength	≥ 15	N/mm2		
Normalised compressive strength	≥ 15	N/mm2		
Bond strength	0.15 / 0.30			
Thermal conductivity	50/50: 0.45 / 90/90: 0.48	W/mK	EN 1745:2012	
Water vapour permeability	5/10			
[Durability : freeze/thaw resistance]	F2			
Water absorption	≤ 18 %	m/md		
Initial rate of water absorption	1.5 - 4.0	kg/(m²min)		
Active soluble salt content	S2			
[Dimensional stability: Moisture movement]	NPD	mm/m		
Dangerous substances	Voldoet		NL-BBK	
Reaction to fire	A1			

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of perfomance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behlaf of the manufacturer by

Atse Blei General Management

Aalst (NL) 30-Jan-2021